


SPOTLIGHTS

LED-Mars

for 3-phase track

ADO Lights by TTC Timmler Technology GmbH
 Christian-Schäfer-Str. 8 | 53881 Flammersheim
 T +49 2255 9212-00 | F +49 2255 9212-99
 info@ado-lights.com | www.ado-lights.com



BASE INFO, PICTURES AND TECHNICAL DRAWINGS



DIMENSIONS	Luminaire housing: 95 x 112 mm [ø x H] Adapter: 168 x 64 x 45 mm [L x W x H]	IP RATING	IP20
POWER CONSUMPTION	Max. 40 W	LUMINAIRE HOUSING	Aluminium powder-coated white, black or grey
LUMINOUS FLUX	Max. 4,000 lm	CONVERTER	Overload protection Overtemperature protection Short-circuit protection
LIGHT BEAM ANGLE	20°/30°/45°/55°	OPTIONS	Track Frosted glass Phase alignment DALI Colour temp. Food premium white or red Colour temp. Food warm white Colour temp. Food fresh white
SERVICE LIFE	LED 50,000 hours at 70% of mean luminous flux	LIGHT CALCULATION	EULUM-Datei see www.ado-lights.com
COLOUR TEMPERATURE	White Kelvin: 2,700/3,000/3,500/4,000/5,000/5,700		
CRI	CRI > 90		
CONTROL INTERFACE	With ballast, not dimmable		

