

DOWNLIGHTS

LED-Cabinet 2

ADO Lights by TTC Timmler Technology GmbH
 Christian-Schäfer-Str. 8 | 53881 Flammersheim
 T +49 2255 9212-00 | F +49 2255 9212-99
 info@ado-lights.com | www.ado-lights.com



BASE INFO, PICTURES AND TECHNICAL DRAWINGS



DIMENSIONS [L X W X H]	Luminaire housing: 145 x 78 x 91 mm Cut-out: 135 x 70 mm
POWER CONSUMPTION	18 W 2 reflectors
LUMINOUS FLUX	1,352lm 1,406lm 1,760lm
LIGHT BEAM ANGLE	42° tilt angle 45° rotatable 355°
SERVICE LIFE	LED 50,000 hours at 70% of mean luminous flux
COLOUR TEMPERATURE	White 2,700/3,000/4,000 Kelvin
CRI	CRI > 90 [CRI > 80]
CONTROL INTERFACE	With ballast, not dimmable
IP RATING	IP44

LUMINAIRE HOUSING	Aluminium white powder-coated or black powder-coated
CONVERTER	Overload protection Overtemperature protection Short-circuit protection
OPTIONS	2 x »Dim to Warm«-LED mit 6 W, 1,200 lm, 2,000–2,800 Kelvin Dimmable ballast 1–10 V DALI Connection cable PoE-enabled
LIGHT CALCULATION	EULUM data see www.ado-lights.com

